ALLOWANCE EQUIPAGE LIST (AEL)

CHARACTERISTICS THIS AEL IS TO REPLACE THE OBA AND OBA CANISTER. REQUIREMENTS CURRENTLY FOUND ON DAMAGE CONTROL AEL 2-880044200 SERIES AND BREATHING APRS-OXY A4 AEL 2-930094060 THRU 2-930094064. THE SELF-CONTAINED BREATHING APPARATUS (SCBA) USES A HIGH PRESSURE AIR CYLINDER WITH A REGULATOR RATED TO SUPPLY BREATHING FUNCTIONS. IT SHALL HAVE A MINIMUM RATED SERVICE TIME OF THIRTY MINUTES AND FORTY-FIVE MINUTES (DEPENDING ON THE SIZE OF THE INSTALLED AIR CYLINDERS). THE SCBA AND ITS ASSOCIATED CHARGING EQUIPMENT (WHICH INCLUDES DIESEL AND/OR ELECTRIC AIR COMPRESSORS) CONSISTS OF HIGH PRESSURE (4500 PSIG) AIR CYLINDER IN A BACKPACK TYPE HARNESS. AIR PRESSURE REGULATORS. FACE MASK AND ASSOCIATED AIR HOSEE. FOR REPAIR PARTS SUPPORT SEE THE FOLLOWING APLS: AIR BSTR PUMP ASSY 990990717 BREATHING AIR TESTER 990580009	DENTIFICATION NO. DATE PAGE
CHARACTERISTICS THIS AEL IS TO REPLACE THE OBA AND OBA CANISTER. REQUIREMENTS CURRENTLY FOUND ON DAMAGE CONTROL AEL 2-880044200 SERIES AND BREATHING APRS-OXY A4 AEL 2-930094060 THRU 2-930094064. THE SELF-CONTAINED BREATHING APPARATUS (SCBA) USES A HIGH PRESSURE AIR CYLINDER WITH A REGULATOR RATED TO SUPPLY BREATHING AIR TO THE USER DURING DAMAGE CONTROL AND FIRE FIGHTING FUNCTIONS. IT SHALL HAVE A MINIMUM RATED SERVICE TIME OF THIRTY MINUTES AND FORTY-FIVE MINUTES (DEPENDING ON THE SIZE OF THE INSTALLED AIR CYLINDERS). THE SCBA AND ITS ASSOCIATED CHARGING EQUIPMENT (WHICH INCLUDES DIESEL AND/OR ELECTRIC AIR COMPRESSORS) CONSISTS OF HIGH PRESSURE (4500 PSIG) AIR CYLINDER IN A BACKPACK TYPE HARNESS. AIR PRESSURE REGULATORS, FACE MASK AND ASSOCIATED AIR HOSEE. FOR REPAIR PARTS SUPPORT SEE THE FOLLOWING APLS: AIR BSTR PUMP ASSY 990990717 BREATHING AIR TESTER 990580009	2-330024108 06-24-03 1 ON BOARD ALLOWANCE TABLE OF COL. COL. COL. COL. COL. COL. COL. COL. COL. COL. COL. COL. COL. COL. COL. COL. COL. COL. COL. COL. COL. B
CHARACTERISTICS THIS AEL IS TO REPLACE THE OBA AND OBA CANISTER. REQUIREMENTS CURRENTLY FOUND ON DAMAGE CONTROL AEL 2-880044200 SERIES AND BREATHING APRS-OXY A4 AEL 2-930094060 THRU 2-930094064. THE SELF-CONTAINED BREATHING APPARATUS (SCBA) USES A HIGH PRESSURE AIR CYLINDER WITH A REGULATOR RATED TO SUPPLY BREATHING AIR TO THE USER DURING DAMAGE CONTROL AND FIRE FIGHTING FUNCTIONS. IT SHALL HAVE A MINIMUM RATED SERVICE TIME OF THIRTY MINUTES AND FORTY-FIVE MINUTES (DEPENDING ON THE SIZE OF THE INSTALLED AIR CYLINDERS). THE SCBA AND ITS ASSOCIATED CHARGING EQUIPMENT (WHICH INCLUDES DIESEL AND/OR ELECTRIC AIR COMPRESSORS) CONSISTS OF HIGH PRESSURE (4500 PSIG) AIR CYLINDER IN A BACKPACK TYPE HARNESS. AIR PRESSURE REGULATORS. FACE MASK AND ASSOCIATED AIR HOSEE. FOR REPAIR PARTS SUPPORT SEE THE FOLLOWING APLS: AIR BSTR PUMP ASSY 990990717 BREATHING AIR TESTER 990580009	ON BOARD ALLOWANCE TABLE ON BOARD ALLOWANCE TABLE OF COL. COL. COL. COL. COL. COL. COL. COL.
CHARACTERISTICS THIS AEL IS TO REPLACE THE OBA AND OBA CANISTER. REQUIREMENTS CURRENTLY FOUND ON DAMAGE CONTROL AEL 2-880044200 SERIES AND BREATHING APRS-OXY A4 AEL 2-930094060 THRU 2-930094064. THE SELF-CONTAINED BREATHING APPARATUS (SCBA) USES A HIGH PRESSURE AIR CYLINDER WITH A REGULATOR RATED TO SUPPLY BREATHING AIR TO THE USER DURING DAMAGE CONTROL AND FIRE FIGHTING FUNCTIONS. IT SHALL HAVE A MINIMUM RATED SERVICE TIME OF THIRTY MINUTES AND FORTY-FIVE MINUTES (DEPENDING ON THE SIZE OF THE INSTALLED AIR CYLINDERS). THE SCBA AND ITS ASSOCIATED CHARGING EQUIPMENT (WHICH INCLUDES DIESEL AND/OR ELECTRIC AIR COMPRESSORS) CONSISTS OF HIGH PRESSURE (4500 PSIG) AIR CYLINDER IN A BACKPACK TYPE HARNESS. AIR PRESSURE REGULATORS, FACE MASK AND ASSOCIATED AIR HOSEE. FOR REPAIR PARTS SUPPORT SEE THE FOLLOWING APLS: AIR BSTR PUMP ASSY 990990717 BREATHING AIR TESTER 990580009	ON BOARD ALLOWANCE TABLE ON BOARD ALLOWANCE TABLE OF COL. COL. COL. COL. COL. COL. COL. COL.
THIS AEL IS TO REPLACE THE OBA AND OBA CANISTER. REQUIREMENTS CURRENTLY FOUND ON DAMAGE CONTROL AEL 2-880044200 SERIES AND BREATHING APRS-OXY A4 AEL 2-930094060 THRU 2-930094064. THE SELF-CONTAINED BREATHING APPARATUS (SCBA) USES A HIGH PRESSURE AIR CYLINDER WITH A REGULATOR RATED TO SUPPLY BREATHING AIR TO THE USER DURING DAMAGE CONTROL AND FIRE FIGHTING FUNCTIONS. IT SHALL HAVE A MINIMUM RATED SERVICE TIME OF THIRTY MINUTES AND FORTY-FIVE MINUTES (DEPENDING ON THE SIZE OF THE INSTALLED AIR CYLINDERS). THE SCBA AND ITS ASSOCIATED CHARGING EQUIPMENT (WHICH INCLUDES DIESEL AND/OR ELECTRIC AIR COMPRESSORS) CONSISTS OF HIGH PRESSURE (4500 PSIG) AIR CYLINDER IN A BACKPACK TYPE HARNESS. AIR PRESSURE REGULATORS. FACE MASK AND ASSOCIATED AIR HOSEE. FOR REPAIR PARTS SUPPORT SEE THE FOLLOWING APLS: AIR BSTR PUMP ASSY 990990717 BREATHING AIR TESTER 990580009	ON BOARD ALLOWANCE TABLE ON BOARD ALLOWANCE TABLE OF COL. COL. COL. COL. COL. COL. COL. COL.
THIS AEL IS TO REPLACE THE OBA AND OBA CANISTER. REQUIREMENTS CURRENTLY FOUND ON DAMAGE CONTROL AEL 2-880044200 SERIES AND BREATHING APRS-OXY A4 AEL 2-930094060 THRU 2-930094064. THE SELF-CONTAINED BREATHING APPARATUS (SCBA) USES A HIGH PRESSURE AIR CYLINDER WITH A REGULATOR RATED TO SUPPLY BREATHING AIR TO THE USER DURING DAMAGE CONTROL AND FIRE FIGHTING FUNCTIONS. IT SHALL HAVE A MINIMUM RATED SERVICE TIME OF THIRTY MINUTES AND FORTY-FIVE MINUTES (DEPENDING ON THE SIZE OF THE INSTALLED AIR CYLINDERS). THE SCBA AND ITS ASSOCIATED CHARGING EQUIPMENT (WHICH INCLUDES DIESEL AND/OR ELECTRIC AIR COMPRESSORS) CONSISTS OF HIGH PRESSURE (4500 PSIG) AIR CYLINDER IN A BACKPACK TYPE HARNESS. AIR PRESSURE REGULATORS. FACE MASK AND ASSOCIATED AIR HOSEE. FOR REPAIR PARTS SUPPORT SEE THE FOLLOWING APLS: AIR BSTR PUMP ASSY 990990717 BREATHING AIR TESTER 990580009	ON BOARD ALLOWANCE TABLE ON BOARD ALLOWANCE TABLE OF COL. COL. COL. COL. COL. COL. COL. COL.
REQUIREMENTS CURRENTLY FOUND ON DAMAGE CONTROL AEL 2-880044200 SERIES AND BREATHING APRS-OXY A4 AEL 2-930094060 THRU 2-930094064. THE SELF-CONTAINED BREATHING APPARATUS (SCBA) USES A HIGH PRESSURE AIR CYLINDER WITH A REGULATOR RATED TO SUPPLY BREATHING AIR TO THE USER DURING DAMAGE CONTROL AND FIRE FIGHTING FUNCTIONS. IT SHALL HAVE A MINIMUM RATED SERVICE TIME OF THIRTY MINUTES AND FORTY-FIVE MINUTES (DEPENDING ON THE SIZE OF THE INSTALLED AIR CYLINDERS). THE SCBA AND ITS ASSOCIATED CHARGING EQUIPMENT (WHICH INCLUDES DIESEL AND/OR ELECTRIC AIR COMPRESSORS) CONSISTS OF HIGH PRESSURE (4500 PSIG) AIR CYLINDER IN A BACKPACK TYPE HARNESS. AIR PRESSURE REGULATORS. FACE MASK AND ASSOCIATED AIR HOSEE. FOR REPAIR PARTS SUPPORT SEE THE FOLLOWING APLS: AIR BSTR PUMP ASSY 990990717 BREATHING AIR TESTER 990580009	COL. COL. COL. COL. COL. COL. COL. COL.
2-880044200 SERIES AND BREATHING APRS-OXY A4 AEL 2-930094060 THRU 2-930094064. THE SELF-CONTAINED BREATHING APPARATUS (SCBA) USES A HIGH PRESSURE AIR CYLINDER WITH A REGULATOR RATED TO SUPPLY BREATHING AIR TO THE USER DURING DAMAGE CONTROL AND FIRE FIGHTING FUNCTIONS. IT SHALL HAVE A MINIMUM RATED SERVICE TIME OF THIRTY MINUTES AND FORTY-FIVE MINUTES (DEPENDING ON THE SIZE OF THE INSTALLED AIR CYLINDERS). THE SCBA AND ITS ASSOCIATED CHARGING EQUIPMENT (WHICH INCLUDES DIESEL AND/OR ELECTRIC AIR COMPRESSORS) CONSISTS OF HIGH PRESSURE (4500 PSIG) AIR CYLINDER IN A BACKPACK TYPE HARNESS. AIR PRESSURE REGULATORS. FACE MASK AND ASSOCIATED AIR HOSEE. FOR REPAIR PARTS SUPPORT SEE THE FOLLOWING APLS: AIR BSTR PUMP ASSY 990990717 BREATHING AIR TESTER 990580009	' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '
2-930094060 THRU 2-930094064. THE SELF-CONTAINED BREATHING APPARATUS (SCBA) USES A HIGH PRESSURE AIR CYLINDER WITH A REGULATOR RATED TO SUPPLY BREATHING AIR TO THE USER DURING DAMAGE CONTROL AND FIRE FIGHTING FUNCTIONS. IT SHALL HAVE A MINIMUM RATED SERVICE TIME OF THIRTY MINUTES AND FORTY-FIVE MINUTES (DEPENDING ON THE SIZE OF THE INSTALLED AIR CYLINDERS). THE SCBA AND ITS ASSOCIATED CHARGING EQUIPMENT (WHICH INCLUDES DIESEL AND/OR ELECTRIC AIR COMPRESSORS) CONSISTS OF HIGH PRESSURE (4500 PSIG) AIR CYLINDER IN A BACKPACK TYPE HARNESS. AIR PRESSURE REGULATORS, FACE MASK AND ASSOCIATED AIR HOSEE. FOR REPAIR PARTS SUPPORT SEE THE FOLLOWING APLS: AIR BSTR PUMP ASSY 990990717 BREATHING AIR TESTER 990580009	' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '
THE SELF-CONTAINED BREATHING APPARATUS (SCBA) USES A HIGH PRESSURE AIR CYLINDER WITH A REGULATOR RATED TO SUPPLY BREATHING AIR TO THE USER DURING DAMAGE CONTROL AND FIRE FIGHTING FUNCTIONS. IT SHALL HAVE A MINIMUM RATED SERVICE TIME OF THIRTY MINUTES AND FORTY-FIVE MINUTES (DEPENDING ON THE SIZE OF THE INSTALLED AIR CYLINDERS). THE SCBA AND ITS ASSOCIATED CHARGING EQUIPMENT (WHICH INCLUDES DIESEL AND/OR ELECTRIC AIR COMPRESSORS) CONSISTS OF HIGH PRESSURE (4500 PSIG) AIR CYLINDER IN A BACKPACK TYPE HARNESS. AIR PRESSURE REGULATORS. FACE MASK AND ASSOCIATED AIR HOSEE. FOR REPAIR PARTS SUPPORT SEE THE FOLLOWING APLS: AIR BSTR PUMP ASSY 990990717 BREATHING AIR TESTER 990580009	
HIGH PRESSURE AIR CYLINDER WITH A REGULATOR RATED TO SUPPLY BREATHING AIR TO THE USER DURING DAMAGE CONTROL AND FIRE FIGHTING FUNCTIONS. IT SHALL HAVE A MINIMUM RATED SERVICE TIME OF THIRTY MINUTES AND FORTY-FIVE MINUTES (DEPENDING ON THE SIZE OF THE INSTALLED AIR CYLINDERS). THE SCBA AND ITS ASSOCIATED CHARGING EQUIPMENT (WHICH INCLUDES DIESEL AND/OR ELECTRIC AIR COMPRESSORS) CONSISTS OF HIGH PRESSURE (4500 PSIG) AIR CYLINDER IN A BACKPACK TYPE HARNESS. AIR PRESSURE REGULATORS, FACE MASK AND ASSOCIATED AIR HOSEE. FOR REPAIR PARTS SUPPORT SEE THE FOLLOWING APLS: AIR BSTR PUMP ASSY 990990717 BREATHING AIR TESTER 990580009	
AND FIRE FIGHTING FUNCTIONS. IT SHALL HAVE A MINIMUM RATED SERVICE TIME OF THIRTY MINUTES AND FORTY-FIVE MINUTES (DEPENDING ON THE SIZE OF THE INSTALLED AIR CYLINDERS). THE SCBA AND ITS ASSOCIATED CHARGING EQUIPMENT (WHICH INCLUDES DIESEL AND/OR ELECTRIC AIR COMPRESSORS) CONSISTS OF HIGH PRESSURE (4500 PSIG) AIR CYLINDER IN A BACKPACK TYPE HARNESS. AIR PRESSURE REGULATORS. FACE MASK AND ASSOCIATED AIR HOSEE. FOR REPAIR PARTS SUPPORT SEE THE FOLLOWING APLS: AIR BSTR PUMP ASSY 990990717 BREATHING AIR TESTER 990580009	
RATED SERVICE TIME OF THIRTY MINUTES AND FORTY-FIVE MINUTES (DEPENDING ON THE SIZE OF THE INSTALLED AIR CYLINDERS). THE SCBA AND ITS ASSOCIATED CHARGING EQUIPMENT (WHICH INCLUDES DIESEL AND/OR ELECTRIC AIR COMPRESSORS) CONSISTS OF HIGH PRESSURE (4500 PSIG) AIR CYLINDER IN A BACKPACK TYPE HARNESS. AIR PRESSURE REGULATORS, FACE MASK AND ASSOCIATED AIR HOSEE. FOR REPAIR PARTS SUPPORT SEE THE FOLLOWING APLS: AIR BSTR PUMP ASSY 990990717 BREATHING AIR TESTER 990580009	
MINUTES (DEPENDING ON THE SIZE OF THE INSTALLED AIR CYLINDERS). THE SCBA AND ITS ASSOCIATED CHARGING EQUIPMENT (WHICH INCLUDES DIESEL AND/OR ELECTRIC AIR COMPRESSORS) CONSISTS OF HIGH PRESSURE (4500 PSIG) AIR CYLINDER IN A BACKPACK TYPE HARNESS. AIR PRESSURE REGULATORS. FACE MASK AND ASSOCIATED AIR HOSEE. FOR REPAIR PARTS SUPPORT SEE THE FOLLOWING APLS: AIR BSTR PUMP ASSY 990990717 BREATHING AIR TESTER 990580009	
CYLINDERS). THE SCBA AND ITS ASSOCIATED CHARGING EQUIPMENT (WHICH INCLUDES DIESEL AND/OR ELECTRIC AIR COMPRESSORS) CONSISTS OF HIGH PRESSURE (4500 PSIG) AIR CYLINDER IN A BACKPACK TYPE HARNESS. AIR PRESSURE REGULATORS, FACE MASK AND ASSOCIATED AIR HOSEE. FOR REPAIR PARTS SUPPORT SEE THE FOLLOWING APLS: AIR BSTR PUMP ASSY 990990717 BREATHING AIR TESTER 990580009	
THE SCBA AND ITS ASSOCIATED CHARGING EQUIPMENT (WHICH INCLUDES DIESEL AND/OR ELECTRIC AIR COMPRESSORS) CONSISTS OF HIGH PRESSURE (4500 PSIG) AIR CYLINDER IN A BACKPACK TYPE HARNESS. AIR PRESSURE REGULATORS, FACE MASK AND ASSOCIATED AIR HOSEE. FOR REPAIR PARTS SUPPORT SEE THE FOLLOWING APLS: AIR BSTR PUMP ASSY 990990717 BREATHING AIR TESTER 990580009	
INCLUDES DIESEL AND/OR ELECTRIC AIR COMPRESSORS) CONSISTS OF HIGH PRESSURE (4500 PSIG) AIR CYLINDER IN A BACKPACK TYPE HARNESS. AIR PRESSURE REGULATORS, FACE MASK AND ASSOCIATED AIR HOSEE. FOR REPAIR PARTS SUPPORT SEE THE FOLLOWING APLS: AIR BSTR PUMP ASSY 990990717 BREATHING AIR TESTER 990580009	
CONSISTS OF HIGH PRESSURE (4500 PSIG) AIR CYLINDER IN A BACKPACK TYPE HARNESS. AIR PRESSURE REGULATORS, FACE MASK AND ASSOCIATED AIR HOSEE. FOR REPAIR PARTS SUPPORT SEE THE FOLLOWING APLS: AIR BSTR PUMP ASSY 990990717 BREATHING AIR TESTER 990580009	
A BACKPACK TYPE HARNESS. AIR PRESSURE REGULATORS, FACE MASK AND ASSOCIATED AIR HOSEE. FOR REPAIR PARTS SUPPORT SEE THE FOLLOWING APLS: AIR BSTR PUMP ASSY 990990717 BREATHING AIR TESTER 990580009	
MASK AND ASSOCIATED AIR HOSEE. FOR REPAIR PARTS SUPPORT SEE THE FOLLOWING APLS: AIR BSTR PUMP ASSY 990990717 BREATHING AIR TESTER 990580009	
AIR BSTR PUMP ASSY 990990717 BREATHING AIR TESTER 990580009	
BREATHING AIR TESTER 990580009	
CCD1 (OC NT) OLDDON	
SCBA (30 MIN CARBON) 99A010025	
SCBA (30 MIN CARBON) 99A010025 SCBA (45 MIN CARBON) 99A010026	
COMPRESSOR, BREATHING AIR 06A990004	
FILTER ASSEMBLY.HP 489980675	
ALL CHANGES TO THIS AEL MUST BE ENDORSED BY THE TYCOM	
AND APPROVED BY NAVSEA DAMAGE CONTROL IN WRITING	
NOTE 1: THE SELF-CONTAINED BREATHING APPARATUS (SCBA)	
CAN BE RECONFIGURED TO EITHER A 30 MMINUTE OR	
45 MINUTE RATING BY EXCHANGING THE CYLINDER INSTALLED IN THE SCBA BACKPACK. THE SCBA	
CONFIGURATION CHANGE WILL BE CONTROLLED BY THE	
DCA OR CHENG, HOWEVER, THE NUMBER OF 30 MINUTE	
OR 45 MINUTE CYLINDERS ONBOARD CANNOT FYCEED THE	
QUANITIES DEFINED WITHIN THIS AFT THE NUMBER	
AND SIZE OF CYLINDERS IS DETERMINED BY ADDING	
CYLINDERS WITHIN AN SCBA AND SPARE CYLINDER	
QUANTITIES LISTED ON THIS AEL.	
NOTE 2: BREATHING AIR REDUCING STATION (BARS),	
ONE PER SHIP; STOWAGE DETERMINED BY DCA. COLUMNS 1 THRU 7 BLANK	
COLUMN 8 FOR LCC-19 CLASS	
REFERENCE NO /DESCRIPTIVE DATA ITEM NAME STOCK NO	
STOCK NC	E O R E E O D T T T T T T T T T T T T T T T T T T
	OCC VS S O
ALLOWANCE EQUIPAGE LIST (AEI	L) 2-330024108 06-24-03 1
SHIP TYPE & HULL NO.	2-330024108 06-24-03 1

ALLOWANCE EQUIPAGE LIST (AEL)

EQUIDACE NOMENOLATURE (CLARA CTCC.	ALLOWA	INCE E	<u>QUIPAGE LIST (A</u>	LEL)									
EQUIPAGE NOMENCLATURE/CHARACTERISTICS		TECHNICAL DOCUMENT	MANUAL	-	IDEN	NTIFIC	ATION	NO.	DA	TE	 -	PAGE	
SCBA, DC-FF SHIPBOARD FOR	LCC-19 CLASS	NUMBER	PLAN										
CHARACTERISTICS		<u> </u>	<u> </u>		2-3	300	241	80	06	-24	-03	2	
CAGE-12004		·		s s 0 0						ED ALLOWANCE TABI			
CCF DATE -12 02				QT UU AT DO UU AT DO RELECTOR S S O MALES U R C C C		İ							
7245940	ATD DCTD DUMP ACCY	74114.4.5		R L CS T Q Q C C N OA E D T L E T V C S T UII Y	COL.	COL.	COL.	COŁ.	COL.	COL.	COL.	COL.	
804861-38	AIR BSTR PUMP ASSY BREATHE APRS, 45MIN CARB	/HH43 1 1 1 12	10-01-465-1507	UPADDD IRAY			Ť			*		2 * -	
6314781	BREATHING AIR RED STA AY	97 42	40-01-485-7705	UPA000 1EEA UPA000 1EAY		i						110	
65 25 960	SEE NOTE 2 BREATHING-AIR TESTER									İ		1	
805004-01	CHARGING WAND ASSEMBLY	9C 47	65-01-473-8300 30-01-468-8025	UPAODD 1REA UPAOZZ 1REA		ŀ			İ			1	
C-D/DV/NAVY	COMPRESSOR, BREATHING AIR	R 7HH43:	10-01-465-1509	UPAODD 1EEA						ĺ	İ	3 3 2 3	
7245961-2 7245961-3	COVER,ABPA COVER,COMPRESSOR	9Z 424	4 0-01-486-6141	UPA OZ Z 1 R EA						ı	i	2	
7245961-1	COVER, HPFA	90 43. 97 42	10-01-468-8384 40-01-486-6121	UPAOZZ 1REA UPAOZZ 1REA					- 1				
804721-01 804722-01	CYLINDER, 30MIN CARBON	9Z 424	10-01-486-1939	UPAOZZ 1REA UPAOZZ 1EEA								3 183	
804871-31	CYLINDER, 45MIN CARBON FACEPIECE, SZ SM	1HS009	99-LL-H55-4954	UPADDO 1EEA						ı		73	
804871-33	FACEPIECE.SZ X-LRG	97 424	10-01-449-3106 10-01-449-3120	UPAOZZ 1EEA								20	
7245941 7245944-1	FILTER ASSEMBLY.HP	7HH433	30-01-472-6835	UPAOZZ 1EEA UPAODD 1RAY						1		10	
7245944-1	HOSE AY/FILTER AIR/H102 HOSE AY, DRIVE AIR, H101	7HH472	20-01-477-1225	UPAODD 1RAY								3 3 3 3	
7245948-1	HOSE AY, FILT/AIR SUPPLY	7HH472	20-01-477-1221 20-01-477-1223	UPAODD 1RAY UPAODD 1RAY					ĺ		Ì	3	
MODEL 1600 39400	KING PELICAN CASE	9Z 676	50-01-491-2762VJ	UPAODD 1RAY XPAOZZ 1REA					ı			3	
39400	WIRE RACK, COLLAPSIBLE	1HM009	9-LL-H52-9120	UPA 02 7 1 E EA								2	
		ΕN	l D					ļ	ŀ	i			
				in the in the last							ļ		
							ļ	i		ĺ			
										-			
						!							
						i	-	l					
						ļ					ŀ		
						1							
	•									ſ			
								İ					
REFERENCE NO/DESCRIPTIVE DATA	ITEM NAME		STOCK NO.						\perp				
			S. OOK NO.	SOUTH OF SOU	1 .	2	3	4	5	6	7	8	
	ALLOWANCE EQUIP	240= 11	CT /AEL	R S OF E T C N V S S O L E T R									
SHIP TYPE & HULL NO.	1 × 1 1	2-3	300	241	08	06-	24-	03	2				
STILE 1 THE & HULL NO.							71		J J -		0.0		